

Compact Lift Tables

X Series fits the need for maximum space efficiency

Chibichan X Capacity 100~750kg

Hydraulic Unit Size



E : 325×350×160



X50C

Foot Pedal Type



X75A-B

Electric Operated Type



2X050510B-B

2-Stage Type

Model	Maximum Capacity	Lifting Height	Table Dimensions (mm)				Motor	Lifting Speed (sec)		Weight	Hydraulic	Cable (m)		High Pressure Hose	
	(kg)	(mm)	Width	Length	Minimum Height	Maximum Height	(kw)	50Hz	60Hz	(kg)	Unit	Power Source	Operating SW	(m)	
3 Phase 200V															
X050406A-B	500	390	460	650	140	530	0.375	14	12	82	E	5.3	5.3	2	
X50SA-B		630			210	840		22	18	111					
X50A-B		750			650	150		800	20	16	126				Internal
X75A-B	28		23	127											
2X050510A-B	500	1,170	235	1,405	29	24		142	4.7	3	—				
Single Phase 100 V															
X10B-B	100	400	500	650	131	531	0.2	12	10	63	Internal	5.3	5.3	—	
X20B-B	200				813	150		715	21	17					66
X25B-B	250				565	140		530	34	28					82
X050406B-B	500	390	460	650	140	530	14	12	58	E					
X50SB-B		630			210	840	22	18	111						
X50B-B		750			650	150	800	20	16	133	Internal	4.7	3	—	
X75B-B	28		23	134											
2X050510B-B	500		1,170	235	1,405	29	24	140							
Foot Pedal Type															
X20C	200	400	500	650	131	531	Foot Pedal Type			55	Internal	Foot Pedal Type			
X25C	250	565		813	715	71									
X50C	500	650		150	800	115									
X75C	750		116												
2X050510C	500	1,170	235	1,405	128										

Mini X Capacity 300~500kg



X050815B

Model	Maximum Capacity	Lifting Height	Table Dimensions (mm)				Motor	Lifting Speed (sec)		Weight	Hydraulic	Cable (m)		High Pressure Hose
	(kg)	(mm)	Width	Length	Minimum Height	Maximum Height	(kw)	50Hz	60Hz	(kg)	Unit	Power Source	Operating SW	(m)
3 Phase 200V														
X030612A-B	300	800	600	1,200	150	950	0.375	16	14	166	Internal	4.7	3	—
X030812A-B			800							191				
X030615A-B		1,000	600	1,500		1,150		20	17	186				
X030815A-B			800							196				
X050612A-B	500	800	600	1,200	150	950	0.375	28	24	168	Internal	4.7	3	—
X050812A-B			800							193				
X050615A-B		1,000	600	1,500		1,150		37	31	190				
X050815A-B			800							200				
Single Phase 100 V														
X030612B-B	300	800	600	1,200	150	950	0.4	19	16	161	Internal	4.7	3	—
X030812B-B			800							186				
X030615B-B		1,000	600	1,500		1,150		25	21	181				
X030815B-B			800							191				
X050612B-B	500	800	600	1,200	150	950	0.4	31	26	163	Internal	4.7	3	—
X050812B-B			800							188				
X050615B-B		1,000	600	1,500		1,150		43	36	185				
X050815B-B			800							195				

Regarding Specifications (see pages 23, 24)

(L) X ○ ○ - B

※Push buttons are standard



Let go and it stops

Super Low Profile Lift Tables

LX Series allows easy loading and unloading of cargo without requiring a below-floor level pit

Capacity 250~3000kg



LX100N-B



LX300N-B

Safety Toe Guard

Minimum Height

LX25 Series ▶ 59mm

LX50 Series ▶ 60mm


LX100 Series ▶ 76mm

LX200 Series ▶ 95mm


LX300 Series ▶ 134mm



Hydraulic Unit is separate from lift table (all Models)



G : 3·1 Phase Unit
W325×L350×H160mm



H : 3 Phase Unit
W360×L430×H176mm



I : 3 Phase Unit
W459×L555×H184mm

Model	Maximum Capacity	Lifting Height	Table Dimensions (mm)				Motor	Lifting Speed (sec)		Weight	Hydraulic	Cable (m)		High Pressure Hose
	(kg)	(mm)	Width	Length	Minimum Height	Maximum Height	(kw)	50Hz	60Hz	(kg)	Unit	Power Source	Operating SW	(m)
3 Phase 200V														
LX25SA-B	250	470	518	810	59	529	0.375	13	11	98	G	5.3	3.5	1.55
LX25LA-B		700		1,010		759		18	15	116				
LX50SA-B	500	470	520	810	60	530		22	19	104				
LX50LA-B		700		1,010		760		33	28	123				
LX100N-B	1,000	900	780	1,280	76	976	0.75	25	21	194	H	5	3	2.5
LX100W-B				215		423		I	5.3	3.5				
LX200N-B	2,000		732	1,350	95	995	1.5				29	24	343	
LX200WM-B			1,000	1,500									450	
LX200WL-B	2,000	417		4.7							2.6	2.5		
LX300N-B	3,000	861	732					1,350	134	31			26	493
LX300WM-B			1,000		1,500	525	2.4							
LX300WL-B					2,000	2.15								
Single Phase 100 V														
LX25SB-B	250	470	518	810	59	529	0.4	11	9	93	G	5.3	3.5	1.55
LX25LB-B		700		1,010		759		16	13	111				
LX50SB-B	500	470		810	60	530		21	18	105				
LX50LB-B		700		1,010		760		31	26	124				